



# MATERIAL SAFETY DATA SHEET

Page 1 of 5

## CHAMPION CHOICE SILICONE LUBRICANT


1. Product And Company Identification			
<b>Supplier</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  Company Contact: Laura E. Radevski Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com		<b>Manufacturer</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  Company Contact: Laura E. Radevski Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	
<b>Supplier Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924		<b>Manufacturer Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924	
Issue Date: 01/18/2011  Product Name: CHAMPION CHOICE SILICONE LUBRICANT Chemical Name: 7-7695-1 MSDS Number: 4856 Product Code: 438-5351 <b>Product/Material Uses</b> - Silicone Lubricant			
2. Composition/Information On Ingredients			
Ingredient Name		CAS Number	Percent Of Total Weight
ACETONE		67-64-1	
BUTANE		106-97-8	
HEPTANE		142-82-5	
PROPANE		74-98-6	
Hazardous components, according to OSHA, are listed when present at 1.0% or greater. Carcinogens are listed when present at 0.1% or greater.			
3. Hazards Identification			
<b>Primary Routes(s) Of Entry</b> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. <b>Eye Hazards</b> - Irritant to eyes. <b>Skin Hazards</b> - Can cause skin irritation after contact with skin. <b>Ingestion Hazards</b> - This is an aerosol product, ingestion is unlikely to occur. Contains petroleum distillate, harmful if swallowed. If accidentally swallowed, do not induce vomiting. Call physician immediately. <b>Inhalation Hazards</b> - Deliberate inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. <b>Chronic/Carcinogenicity Effects</b> - Overexposure to solvents have been associated with nervous system damage. None of the ingredients, present in excess of 0.1%, are listed as carcinogenic by NTP, IARC or OSHA <b>Teratogenicity (Birth Defects)</b> - Not known. <b>Reproductive Effects</b> - Not known. <b>Neurotoxicity</b> - Not known. <b>Mutagenicity (Genetic Effect)</b> - Not known. <b>Signs And Symptoms</b> - Acute: Deliberate inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Contact with skin can cause irritation. Irritant to the eyes. <b>Conditions Aggravated By Exposure</b> - May aggravate pre-existing skin and respiratory disorders.			

## CHAMPION CHOICE SILICONE LUBRICANT

### 3. Hazards Identification - Continued

**Conditions Aggravated By Overexposure** - May aggravate pre-existing skin and respiratory disorders.

### First Aid (Pictograms)



### 4. First Aid Measures

**Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**Skin** - Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

**Ingestion** - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillate. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

**Inhalation** - If overcome by vapor move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

### 5. Fire Fighting Measures

**Flash Point:** Not available °F Not available °C

**Flash Point Method:** Not available

**Lower Explosive Limit:** Not available

**Upper Explosive Limit:** Not available

**Fire And Explosion Hazards** - This product is an aerosol product for which **Flame Projection is over 18 in. with 5 in. flashback.** Temperatures above 120 F may cause cans to burst.

**Extinguishing Media** - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

**Fire Fighting Instructions** - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

### 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

### Handling & Storage (Pictograms)



### 7. Handling And Storage

**Handling And Storage Precautions** - Store in a cool, dry place away from heat and open flame.

**Handling Precautions** - Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.

**Storage Precautions** - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B)**

**Work/Hygienic Practices** - Wash hands thoroughly after using this product.

## CHAMPION CHOICE SILICONE LUBRICANT

### 7. Handling And Storage - Continued

#### Protective Clothing (Pictograms)



### 8. Exposure Controls/Personal Protection

**Engineering Controls** - Use with adequate general and local exhaust ventilation.

**Eye/Face Protection** - Conventional eyeglasses to guard against splashing.

**Skin Protection** - Nitrile rubber gloves required.

**Respiratory Protection** - Use in well-ventilated area ONLY. **When using indoors, keep windows and doors open until fumes dissipate.**

#### Ingredient(s) - Exposure Limits

ACETONE

PEL 750 ppm ; TWA/TLV 750ppm

BUTANE

ACGIH TLV-TWA 800 ppm

HEPTANE

ACGIH TLV-STEL 500 ppm ; ACGIH TLV-TWA 400 ppm ; OSHA PEL-TWA 500 ppm

PROPANE

ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm

### 9. Physical And Chemical Properties

**Appearance** - Clear liquid.

**Odor** - Petroleum hydrocarbon and acetone odor.

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** Not applicable °F Not applicable °C

**Boiling Point:** Acetone 133 °F Acetone 56 °C

**Specific Gravity:** 0.747 concentrate

**Percent VOCs:** 58.84

**pH Factor:** NA

**Solubility:** Insoluble

**Evaporation Rate:** Faster than butyl acetate

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

**Conditions To Avoid (Stability)** - Temperatures above 120 F

**Incompatible Materials** - Avoid heat, open flame and contact with strong oxidizers.

**Hazardous Decomposition Products** - Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

**Conditions To Avoid (Polymerization)** - Temperatures above 120 F

### 11. Toxicological Information

No Data Available...

## CHAMPION CHOICE SILICONE LUBRICANT

### 12. Ecological Information

**Ecotoxicological Information** - No specific ecological data is available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

### 13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** Place in trash or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

### 14. Transport Information

**Proper Shipping Name** - ORM-D Consumer Commodity

**Hazard Class**

2.1

**DOT Identification Number**

UN1950

**DOT Shipping Label**

Aerosol Consumer Commodity

### 15. Regulatory Information

**U.S. Regulatory Information** - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**SARA Hazard Classes**

Acute Health Hazard; Fire Hazard

**SARA Section 313 Notification** - This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

**Ingredient(s) - State Regulations**

BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

HEPTANE

New Jersey - Workplace Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance


PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

# MATERIAL SAFETY DATA SHEET

Page 5 of 5

## CHAMPION CHOICE SILICONE LUBRICANT

<b>NFPA</b> 	<b>HMIS</b> <table border="1"><tr><td>HEALTH</td><td>2</td></tr><tr><td>FLAMMABILITY</td><td>4</td></tr><tr><td>REACTIVITY</td><td>1</td></tr><tr><td>PERSONAL PROTECTION</td><td>B</td></tr></table>	HEALTH	2	FLAMMABILITY	4	REACTIVITY	1	PERSONAL PROTECTION	B
HEALTH	2								
FLAMMABILITY	4								
REACTIVITY	1								
PERSONAL PROTECTION	B								

### 16. Other Information

#### Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supersedes A Previous MSDS Dated: 06/28/2005

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Chase Products Co.